





# ADVANCED and INSPECTION

#### **DAVID BROWER**

FOR DEEPWATER OIL AND GAS

**ASTRO TECHNOLOGY** 712 Main Street, Suite 3200 Houston, Texas 77002 281.464.0100

dbrower@astrotechnology.com





#### **FAILURES TO MONITOR AND PREDICT**

- Detect early warning signs
- Automate monitoring of critical systems
- Give critical data to key decision makers



**Deepwater Horizon** 2010



**Thunder Horse** 2005




**Texas City Refinery** 2005





# **SMALL LEAKS IN SUBSEA FIELDS**







#### THE NEED FOR BETTER SUBSEA INSTRUMENTATION

#### **Prevent Undesired Events from Happening**

- Detect warning signs early
- Prevent potential accidents from occurring
- Improve system operations
- Automate monitoring of critical systems
- Track pressure, temperature, strain and flow
- Give critical data to key decision makers
- Eliminate production downtime
- Prevent asset damage and pipeline leaks
- Reduce safety and environmental risks





# FROM AEROSPACE TO SUBSEA

**Clear Gulf Study** 








# **ABOUT CLEAR GULF STUDY**

#### **Prevention of Unwanted Events, Rather than Reaction**

#### **ADVANCED INSTRUMENTATION FOR:**

- Subsea fields
- Pipelines and risers
- LNG facilities



#### **CLEAR GULF FOCUS AREAS:**

- Risers and Flowlines
- Flow Assurance
- Subsea Equipment Monitoring
- Miniature Subsea Robotics

- Leak Detection
- Smart Fields (Intelli-Fields)
- **Downhole Monitoring**
- Mooring Line Monitoring

- Arctic Monitoring
- Service Life Extension





#### **ADVANTAGES OF CLEAR GULF**

#### **Prevention of Anomalies**


- Improve performance
- Reduce risk environmental and safety
- Involvement in advanced technology research for oil and gas
- NASA collaboration
- Outside research institutions involvement, i.e. multiple universities
- Industry "subject-matter experts" interface
- Participation on "Technical Steering Committee"
- Access to leading-edge technology
- Significant cost benefit pooling funding resources
- Acts as an R&D department for oil and gas companies
  - Supplements R&D efforts at large companies
  - Provides new R&D departments for smaller, independent companies
- Participate in annual meeting with U.S. Congress





#### FIBER-OPTIC SENSOR ROCKET MOTOR TEST

#### **Fiber-Optic Pressure Gauge Validation**










#### **INSTRUMENTATION OF NASA'S ROBONAUT HAND**














TROIKA - GULF OF MEXICO

ASTRO TECHNOLOGY pioneered the use of fiber-optic sensors on a subsea pipeline to monitor pressure, strain and vibration in external casing pipe bundle during fabrication.










# **BASS LITE - DEVIL'S TOWER**



- Located in Atwater Valley Block 426
- Utilizes 20.3-cm (8-in) diameter flowline
- 90-km (56-mi) length
- Ties to Devil's Tower in Mississippi Canyon
- Production Up to 130 million cubic feet per day
- Water depth -2,050 m (6,750 feet)
- Commenced operation in February 2008

#### **MONITORING:**


Pressure **Temperature** Well 1 Hoop and Axial Strain 18 miles 36 miles 56 miles FLET FLMT1 FLMT2





# FIBER-OPTIC SENSORS FOR DEEPWATER DRILLING **Ocean Clipper**











#### PREVIOUS INSTRUMENTATION ON DEEPWATER RISERS







#### PREVIOUS INSTRUMENTATION ON RISERS AND FLOWLINES














# DEVELOPMENTS






# **OVERVIEW OF NEW DEVELOPMENTS**

- New tensile strength measurements
- Quantified effects of wet and dry bonding
- Improved clamp design
- Methods for calibration of post-installed sensors






# **TENSION LEG MONITORING SYSTEM**







# **TTMS CLAMP**








#### SUBSEA BONDING STRENGTH ENSURED

#### **Button Pull Testing**










# **BONDING MAINTAINED**

**Four-Point Bending Test** 








# **BONDING MAINTAINED**

#### **Compression and Tension Tests**








# TENSILE STRENGTH MEASURED


#### **Button Pull Testing**







# **SUMMARY OF TENSILE STRENGTH RESULTS**







# **SUMMARY OF TENSILE STRENGTH RESULTS**


Clamp	Avg (psi)	StDev (psi)	Min (psi)	Max (psi)	Description
ВВ	292.0	108.9	113.6	498.6	Dry Bonded Control
AA	81.4	47.2	31.1	193.5	Wet Bonded Control
A	94.0	30.4	45.0	155.8	Four Point Bending (Left)
В	174.1	112.4	29.8	503.3	Four Point Bending (Left)
E	91.1	46.9	49.5	150.8	Four Point Bending (Center)
С	142.5	65.6	45.8	267.9	Four Point Bending (Right)
D	136.3	73.6	57.5	358.7	Four Point Bending (Right)
F	114.0	53.7	33.6	225.7	Tension
G	105.3	59.8	29.7	268.8	Compression





# **IMPROVED CLAMP DESIGN**






**Prototype Clamp Mold Created with 3D Printer** 








# **CALIBRATION OF POST-INSTALLED SENSORS**







# THERMOCLINE AT SENSOR CLAMP DEPTH








# PREDICTIVE MONITORING

#### **Foxtrot TTMS Average Load**








# PREDICTIVE MONITORING

#### **Foxtrot TTMS Average Load**



# CLEAR GULF

#### A COLLABORATION BETWEEN

the Oil and Gas Industry,
NASA and Astro Technology

































**PROPOSED PARTNERS** 

- Create cutting-edge techniques for managing production
- Develop safer and more environmentally sensitive systems for drilling and production
- Respond to challenges faced when working in remote and harsh environments
- Focus on monitoring assets including platforms, risers, flowlines, subsea equipment, deepwater wells and downhole operations





